



**FF400 SALLYPORT/SECURITY (SOLID SHEETED)
 FOUR-FOLD DOOR GENERAL LAYOUT
 OPERATOR: R-SERIES, ELECTRO-MECHANICAL**

This layout is designed as a guide for required clearances for our standard Four-Fold Door systems. Contact us to discuss the wide variety of options available and for custom clearance requirements or larger opening sizes.

DOOR WIDTHS	CLEARANCES				MAX. TIME TO OPEN	MOTOR HP	OPERATOR SIZE
	A	B	C	D			
7'-6" to 10'-6"	13"	15"	29"	15"	5.3 sec	1/2	R1
10'-6" to 13'-6"	15"	15"	40"	16"	7.7 sec	1/2	R2
13'-6" to 16'-0"	15"	15"	42"	16"	7.7 sec	3/4	R3
16'-0" to 17'-3"	15"	15"	42"	17"	11.2 sec	3/4	R3-10"
17'-3" to 23'-0"	21"	15"	65"	18"	15.4 sec	1	R3.5

*Consult manufacturer for larger sizes or modified clearances



400 West Cherry Street,
 P.O. Box 5
 Kasota, MN 56050-0005

Phone: 507-931-6910
 Fax: 507-931-9318
 Toll Free: 800-959-1352